

This redlined draft, generated by CompareRite (TM) - The Instant Redliner, shows the differences between -

original document : C:\WINDOWS\TEMP\HRT_578026_1
and revised document: C:\WINDOWS\TEMP\HRT_578028_1

CompareRite found 14 change(s) in the text

Deletions appear as Overstrike text

Additions appear as Bold text



A

BLACK-LINED VERSION OF CLAIMS

1. A jewelry clasp comprising:

(a) first and second elongated legs;

(b) a receptor at one end of said first leg and

having a pair of spaced side walls providing a channel-shaped recess for receiving the adjacent end of said second leg, said recess being dimensioned to seat said adjacent end of said second leg snugly, at least one of said side walls having a portion projecting transversely of said channel-shaped recess towards the other of said side walls at a point spaced from the base of said channel to provide the a retention area therebelow and to provide a restriction in said channel-shaped recess to reduce the width of the channel to less than the width of said second leg, at least one of said side walls flexing outwardly as said second leg is pressed against said projecting portion to allow said second leg to pass thereby, said second leg being retained in said retention area of said channel-shaped recess by said projecting portion after said second leg has passed thereby towards the base of said channel; and

(c) means connecting the other ends of said first and second legs.

A

2. A jewelry clasp comprising:

(a) first and second elongated legs;

(b) a receptor at one end of said first leg and having a pair of spaced side walls providing a channel-shaped recess for receiving the adjacent end of said second leg, said recess being dimensioned to seat said adjacent end of said second leg snugly, one of the side walls of said receptor is of greater length than the other end and has its outer end bent over the other of said side walls to provide a restricted lateral opening into said channel through which said second leg may be introduced, at least one of said side walls having a portion projecting towards the other of said side walls to provide a restriction in said channel-shaped recess to reduce the width of the channel to less than the width of said second leg, at least one of said side walls flexing as said second leg is pressed against said projecting portion to allow said second leg to pass thereby, said second leg being retained in said channel-shaped recess by said projecting portion; and

(c) means connecting the other ends of said first and second legs.

A

~~2. A jewelry clasp in accordance with Claim 1 wherein one of the side wealls of said receptor is of greater length than the other end and has its outer end bent over the other of said side walls to provide a restrieted lateral opening into said channel through which said second leg may be introduced.~~

3. A jewelry clasp in accordance with Claim 1 wherein said legs are integrally formed with a spring coiled portion at said other ends thereof, said spring coiled portion biasing said one end of said second leg towards said first leg and said receptor.

4. A jewelry clasp in accordance with Claim 1 wherein the flexing of said one side wall of said receptor to permit said second leg to pass by said projecting portion produces an audible clicking sound.

5. A jewelry assembly comprising:

(a) at least two elongated chains each having elements providing passages therethrough; and

(b) a clasp having:

(i) first and second elongated legs extending in spaced relationship and through passages in elements in each of said chains;

(ii) a receptor at one end of said first leg and having a pair of spaced side walls providing a channel-shaped recess for receiving the adjacent end of said second leg, said recess being dimensioned to seat said adjacent end of said second leg snugly, at least one of said side walls having a portion projecting **transversely of said channel shaped recess** towards the other of said side walls **at a point spaced from the base of said channel to provide a retention area therebelow** and to provide a restriction in said channel-shaped recess to reduce the width of the channel to less than the width of said second leg, at least one of said side walls flexing **outwardly** as said second leg is pressed against said projecting portion to allow said second leg to pass thereby, said second leg being retained in said ~~channel by said projecting~~ **retention area of said channel-shaped recess by said**

A

projecting portion after said second leg has passed
thereby towards the base of said channel; and

(iii) means connecting the other ends of said
first and second legs, whereby said chains are
retained on said second leg between said receptor and
said connecting means.

A

6. ~~The jewelry assembly in accordance with Claim 5~~
wherein A jewelry assembly comprising:

(a) at least two elongated chains each having
elements providing passages therethrough; and

(b) a clasp having:

(i) first and second elongated legs extending
in spaced relationship and through passages in
elements in each of said chains;

(ii) a receptor at one end of said first leg and
having a pair of spaced side walls providing a
channel-shaped recess for receiving the adjacent end
of said second leg, said recess being dimensioned to
seat said adjacent end of said second leg snugly, one
of the side walls of said receptor ~~is~~ being of greater
length than the other end and ~~has~~ having its outer end
bent over the other of said side walls to provide a
restricted lateral opening into said channel through
which said second leg may be introduced, at least one
of said side walls having a portion projecting towards
the other of said side walls to provide a restriction
in said channel-shaped recess to reduce the width of
the channel to less than the width of said second leg,
at least one of said side walls flexing as said second
leg is pressed against said projecting portion to

A

allow said second leg to pass thereby, said second leg being retained in said channel-shaped recess by said projecting portion; and

(iii) means connecting the other ends of said first and second legs, whereby said chains are retained on said second leg between said receptor and said connecting means.

A

7. The jewelry assembly in accordance with Claim 5 wherein said legs are integrally formed with a spring coiled portion at other ends thereof, said spring coiled portion biasing said one end of said second leg towards said first leg and said receptor.

8. The jewelry assembly in accordance with Claim 5 wherein the flexing of said one side wall of said receptor to permit said second leg to pass by said projecting portion produces an audible clicking sound.

9. The jewelry assembly in accordance with Claim 5 wherein said elements in said chains comprise loops at the ends thereof.